

▶ Twisted Rope and Wicking

DESCRIPTION



NOR-FAB twisted rope is twisted strands of soft, pliable fibers that provide a general utility product with varied industry applications. Rope is formed by twisting two or more bound strands of wicking into a flexible, resilient packing for use where a thicker than wicking material is desired.



APPLICATIONS



- Excellent packing for steam valves, and metal wipe in tinning and galvanizing.

FEATURES



- Inherently Flame Resistant
- Excellent Strength and Abrasion Resistance
- Good Flexibility
- Good Chemical Resistance
- Excellent Mildew Resistance
- Heat Resistant up to 650°F
- Synthetic Blend



P.O. Box 454, 253 Darco Drive
Independence, VA 24348 USA
T: 1-276-773-2711 / F: 1-276-773-0208
www.DavlynGroup.com

▶ Wick

Standard: Approximately 25lb Coils

Style Number	Size ID	Feet./LB	Put-Up
400W-1250-25*	1/8"	370.0	3lb pkgs.
400W-1560-28	5/32"	275.0	3lb pkgs.
400W-1875-29**	3/16"	175.0	6lb pkgs.
400W-2500-01	1/4"	106.0	16lb pkgs.
400W-3750-02	3/8"	71.0	16lb pkgs.

Weight & Size Tolerance +/- 10%

* Order in 18lb. Increments. May be on tubes or spools.

** Order in 12lb. Increments. May be on tubes or spools.

▶ Twisted Rope

Approximately 16lb Spools

Style Number	Size ID	Ft./LB	Ft./16lb Spool
400R-2500-1	1/4"	72.0	1,152
400R-3750-02	3/8"	38.0	608

Standard: Approximately 25lb Coils

Style Number	Size ID	Ft./LB	Ft./25lb Spool
400R-4375-03	7/16"	29.0	725
400R-5000-04	1/2"	28.0	700
400R-6250-05	5/8"	19.0	475
400R-7500-06	3/4"	12.5	312.5
400R-8750-07	7/8"	10.0	250
400R-1000-08	1"	8.4	210

Weight and Size Tolerance +/- 10%

Rope available without glue @ 5% extra charge.

Approximately 13lb spools available @ 10% charge.



P.O. Box 454, 253 Darco Drive
 Independence, VA 24348 USA
 T: 1-276-773-2711 / F: 1-276-773-0208
www.DavlynGroup.com