## CHOICE® ALUMINIZED FABRICS 07TT217-AL7

A Norfab woven fabric of an Aramid/OPF fiber blend, aluminized one side. Applications include light weight safety clothing, gloves, mitts, jacket, and other industrial applications. Resistant to reflected heat sources, offers very good thermal protection for safety garments.

## **About NOR\*FAB Corporation**

NOR\*FAB manufactures textile products using flame resistant synthetic fibers suited for use at high temperatures and for personal protection. These items include broad woven roll goods and narrow products in the form of woven and knitted tapes, sleeving, rope, and gasketing. NOR\*FAB uses para-aramid, meta-aramid, melamine, phenolic, oxidized PAN, flame resistant rayon, polybenzimideazole, and other technical fibers blended into unique yarns which provide high levels of heat protection and insulation.

NOR\*FAB produces many of these yarns on the DREF Spinning System for use in the weaving, knitting, gasket, and wire & cable industries. NOR\*FAB possesses the largest collection of DREF III spinning frames of any yarn manufacturer in the world.

## Among its offerings, NOR\*FAB boasts fabric lines for the following end uses:

Firefighting

OMNI Vantage<sup>™</sup>, OMNI Elite®, OMNI 45<sup>™</sup>, and OMNI Quilt<sup>™</sup>

**Electric Arc Protection** 

NF  $Arc^{\mathsf{TM}}$ ,  $ArcWeld^{\mathsf{R}}$ 

**Welding Protection** 

ArcWeld®

**Cut Protection** 

CutPro®

**Molten Metal Splash Protection** 

Choice®

## **Since 1979**

Proud American Manufacturers of Flame Resistant Textiles



NORFAB AL7 Aluminized Fabric Data Sheet	
Style	07TT217-40-AL7
Base Fabric	Aramid cover with OPF insert
Color/Appearance	Light Green, Aluminized 1 side
Style	Twill
Fabric Weight (oz/yd², average)	8.5 oz (288 gm/m²)
Fabric Thickness, (in)	0.017
Warp Strength (lbs) (1" unraveled)	188
Fill Strength (lbs) (1" unraveled)	176
Flammability-After Flame (seconds)	0
Flammability- Char length (inches)	0.5
Adhesion after Wet Flex	Pass
Reflectivity after Abrasion (seconds)(ASTM F1939)	29
RPP Rating (cal/cm²)	58
Taber Abrasion	1300
Molten Aluminum Splash (ASTM F955)	Pass

All data +/- 10%. All data intended as general information and no warranties, guarantees, or claims of fitness for use are expressed or implied by NOR\*FAB Corp. 514



Box 830, Norristown, PA 19404-0830 U.S.A.
Tel: 610-275-7270 • 800-441-9680 • Fax: 610-277-6106
Email: sales@norfab.com • www.norfab.com