

CHOICE® ALUMINIZED FABRICS *16HT65-AL7*

A Norfab woven fabric of an Aramid fiber blend over an oxidized PAN (OPF) core yarn, aluminized one side. Applications include safety clothing, gloves, mitts, jackets, curtains and other industrial applications. Resistant to radiant heat sources, offers excellent thermal protection for safety garments. Recommended for molten metal splash protection.

About NOR*FAB Corporation

NOR*FAB manufactures textile products using flame resistant synthetic fibers suited for use at high temperatures and for personal protection. These items include broad woven roll goods and narrow products in the form of woven and knitted tapes, sleeving, rope, and gasketing. NOR*FAB uses para-aramid, meta-aramid, melamine, phenolic, oxidized PAN, flame resistant rayon, polybenzimidazole, and other technical fibers blended into unique yarns which provide high levels of heat protection and insulation.

NOR*FAB produces many of these yarns on the DREF Spinning System for use in the weaving, knitting, gasket, and wire & cable industries. NOR*FAB possesses the largest collection of DREF III spinning frames of any yarn manufacturer in the world.

Among its offerings, NOR*FAB boasts fabric lines for the following end uses:

Firefighting

OMNI Vantage™, OMNI Elite®, OMNI 45™, and OMNI Quilt™

Electric Arc Protection

NF Arc™, ArcWeld®

Welding Protection

ArcWeld®

Cut Protection

CutPro®

Molten Metal Splash Protection

Choice®

Since 1979

Proud American Manufacturers of Flame Resistant Textiles



NORFAB AL7 Aluminized Fabric Data Sheet

Style	16HT65-AL7
Base Fabric	Aramid/OPF
Color/Appearance	Light Green, Aluminized 1 side
Style	Herringbone Twill
Fabric Weight (oz/yd², average)	19 (644 g/m ²)
Fabric Thickness, (in)	0.045
Warp Strength (lbs)	250
Fill Strength (lbs)	170
Flammability-After Flame (sec)	0
Flammability- Char length (in)	0.2
Adhesion after Wet Flex	Pass
Reflectivity after Abrasion (sec) (ASTM F1939)	32
RPP Rating (cal/cm²)	64
Taber Abrasion	1700
Molten Iron Splash (ASTM F955)	Pass
Molten Aluminum Splash (ASTM F955)	Pass
Other Certifications	ISO 11612 (2015) A1, A2, B1, C4, D3, E3, F1

All data +/- 10%. All data intended as general information and no warranties, guarantees, or claims of fitness for use are expressed or implied by NORFAB Corp. 514



1310 Stanbridge Street,

Box 830, Norristown, PA 19404-0830 U.S.A.

Tel: 610-275-7270 • 800-441-9680 • Fax: 610-277-6106

Email: sales@norfab.com • www.norfab.com