

## ▶ Series 400 Tapes

### DESCRIPTION



**NOR · FAB Series 400 Tapes** are carefully woven and sized using para-aramid fiber blends over a fiberglass core yarn.



### APPLICATIONS



- **Lagging of all types**
- **Pipe Insulation wrap**
- **Electrical insulation**
- **Thermal Insulation**
- **Gasketing**

### FEATURES



- Inherently Flame Resistant
- DREF Yarn Construction
- Excellent Strength and Abrasion Resistance
- Good Flexibility
- Good Chemical Resistance
- Excellent Mildew Resistance
- Heat Resistant up to 650°F
- Synthetic Blend



P.O. Box 454, 253 Darco Drive  
Independence, VA 24348 USA  
T: 1-276-773-2711 / F: 1-276-773-0208  
[www.DavlynGroup.com](http://www.DavlynGroup.com)

## ▶ Series 400 Tapes

		<b>N11P400</b>	<b>N22P400</b>	<b>N44P400</b>	<b>N88P400</b>
<b>Tape Thickness</b>		<b>1/32"</b>	<b>1/16"</b>	<b>1/8"</b>	<b>1/4"</b>
<b>Width</b>	<b>Code</b>	<b>Lbs./100ft</b>	<b>Lbs./100ft</b>	<b>Lbs./100ft</b>	<b>Lbs./100ft</b>
<b>1/2"</b>	<b>04</b>	0.32	0.54	**1.20	**2.28
<b>3/4"</b>	<b>06</b>	0.45	0.85	1.73	*3.33
<b>1"</b>	<b>08</b>	0.60	1.11	2.33	4.55
<b>1 1/2"</b>	<b>10</b>	0.90	1.66	3.41	6.91
<b>2"</b>	<b>12</b>	1.21	2.22	4.49	9.25
<b>2 1/2"</b>	<b>14</b>	1.50	2.78	5.58	11.61
<b>3"</b>	<b>16</b>	1.82	3.33	6.66	13.90
<b>4"</b>	<b>20</b>	*2.42	4.45	*9.05	18.67
<b>5"</b>	<b>21</b>	*3.02	5.55	*11.22	23.37
<b>6"</b>	<b>22</b>	*3.63	6.66	*13.39	27.54
<b>7"</b>	<b>46</b>	4.23	7.77	15.72	32.09
<b>8"</b>	<b>23</b>	4.83	8.88	18.05	36.64
<b>9"</b>	<b>72</b>	—	9.99	20.3	41.19
<b>10"</b>	<b>80</b>	—	11.11	22.71	45.74
<b>11"</b>	<b>88</b>	—	12.21	25.04	50.29
<b>12"</b>	<b>96</b>	—	13.32	27.37	54.84

Weight and Size Tolerance +/- 10%

\*\* Two 50ft. Rolls packed together

To order tape, select thickness and width you require. Identify the code number for proper tape width. This is the suffix of the order part number. Example: you wish to order 1/16" thick tape at a width of 2". The 1/16" thickness is tape N22P400. The width code for 2" wide tape is 12. Therefore, specify N22P400-12 tape.

#### Notes:

- Roll lengths 100 feet unless otherwise specified.
- Pressure Sensitive Adhesive (PSA) available up to 3" tape widths
- Items marked above with an asterisk (\*) must be minimum of 5 roll order.
- Other tape widths available in minimum quantities of 20 rolls per order.
- All tapes may be Vertex (Vermiculite coated for an additional coating charge.)



P.O. Box 454, 253 Darco Drive  
 Independence, VA 24348 USA  
 T: 1-276-773-2711 / F: 1-276-773-0208  
[www.DavlynGroup.com](http://www.DavlynGroup.com)