Woven Sleeving

APPLICATIONS

NOR · FAB Woven Sleeving is manufactured in two styles. The Series 400 sleeving is para-aramid fibers over fiberglass core yarn. Series 1200 is produced using a combination of PBI fiber and cardable glass fibers spun over a fiberglass core yarn.



Electrical Leads
Cables and Other
Conductors to Provide

Abrasion Resistance as well

as Fire Protection

Many Other Uses

- Inherently Flame Resistant
- DREF Yarn Construction
- Excellent Strength and Abrasion Resistance
- · Good Flexibility

FEATURES

- Good Chemical Resistance
- Excellent Mildew Resistance
- Synthetic Blend
- Heat Resistant up to 650°F



P.O. Box 454, 253 Darco Drive Independence, VA 24348 USA T: I-276-773-2711 / F: I-276-773-0208 www.DavlynGroup.com

• Woven Sleeving

| Series 400 I/I6" Wall Thickness I 00% para-aramid over fiberglass core yarn | | | |
|---|---------|----------|--|
| Style Number | Size ID | Feet./LB | |
| 400WS0375-2 | 3/8" | 46.9 | |
| 400WS0750-2 | 3/4" | 26.7 | |
| 400WS1000-2 | ١" | 20.4 | |
| 400WS1125-2 | I I/8" | 18.8 | |
| 400WS1250-2 | /4" | 17.1 | |
| 400WS1500-2 | I I/2" | 14.7 | |
| 400WS2000-2 | 2" | 9.7 | |

| Series 1200 3/32" Wall Thickness A blend of PBI fibers and cardable glass over fiberglass core yarn | | | |
|---|---------|----------|--|
| Style Number | Size ID | Feet./LB | |
| I 200WS03 I 3-3 | 5/16" | 26.7 | |
| I 200WS0375-3 | 3/8" | 23.3 | |
| I200₩S0500-3 | 1/2" | 18.5 | |
| I 200WS0625-3 | 5/8" | 16.2 | |
| I200₩S0750-3 | 3/4" | 13.4 | |
| 1200WS1000-3 | ١" | 10.5 | |
| 1200WS1500-3 | I I/2" | 7.4 | |

Other size may be available. Minimum quantities may apply. All data +/- 10%



P.O. Box 454, 253 Darco Drive Independence, VA 24348 USA T: I-276-773-2711 / F: I-276-773-0208 www.DavlynGroup.com